## TECHNICAL DATA SHEET



## **BBKS-4317 Blown Stretch Film**

Product data - raw material - colour - colour - roll width - roll width tolerance - roll length - roll length - roll length tolerance - roll length tolerance - film thickness - film thickness tolerance - core type - core diameter  Technical data - elongation at break - dart impact - pre-stretch - yield  Packing data - rolls per case - case weight  LLDPE Black - 400mm - 200mm - 20	Product description	Stretch wrap film for manual use, on extended core
~ colour  ~ roll width  ~ roll width tolerance  ~ roll length  ~ roll length  ~ roll length tolerance  ~ film thickness  ~ film thickness  17mu  ~ film thickness tolerance  ~ core type  ~ core diameter  Technical data  ~ elongation at break  ~ dart impact  ~ pre-stretch  ~ tensile strength  ~ yield  Packing data  ~ rolls per case  6	Product data	
~ roll width 400mm  ~ roll width tolerance ±5mm  300mtr  ~ roll length 300mtr  ~ roll length tolerance +/- 2.0%  ~ film thickness 17mu  ~ film thickness tolerance ±10%  ~ core type Extended  ~ core diameter 38mm  Technical data  ~ elongation at break 410%  ~ dart impact 60g  ~ pre-stretch 0-100%  ~ tensile strength 37Mpa  ~ yield 64.3m²/kg	~ raw material	LLDPE
<ul> <li>roll width tolerance</li> <li>roll length</li> <li>roll length tolerance</li> <li>film thickness</li> <li>film thickness tolerance</li> <li>core type</li> <li>core diameter</li> <li>Extended</li> <li>rore diameter</li> <li>38mm</li> </ul> Technical data <ul> <li>elongation at break</li> <li>dart impact</li> <li>pre-stretch</li> <li>rensile strength</li> <li>yield</li> </ul> Packing data <ul> <li>rolls per case</li> </ul> Description <ul> <li>domination</li> <li>domination</li></ul>	~ colour	Black
<ul> <li>roll length</li> <li>roll length tolerance</li> <li>film thickness</li> <li>film thickness tolerance</li> <li>film thickness tolerance</li> <li>core type</li> <li>core diameter</li> <li>Technical data</li> <li>elongation at break</li> <li>dart impact</li> <li>pre-stretch</li> <li>tensile strength</li> <li>yield</li> <li>Packing data</li> <li>rolls per case</li> <li>6</li> </ul>	~ roll width	400mm
- roll length tolerance +/- 2.0% - film thickness 17mu - film thickness tolerance ±10% - core type Extended - core diameter 38mm  Technical data - elongation at break 410% - dart impact 60g - pre-stretch 0-100% - tensile strength 37Mpa - yield 64.3m²/kg	~ roll width tolerance	±5mm
<ul> <li>film thickness</li> <li>film thickness tolerance</li> <li>core type</li> <li>core diameter</li> <li>Extended</li> <li>38mm</li> <li>Technical data</li> <li>elongation at break</li> <li>dart impact</li> <li>pre-stretch</li> <li>tensile strength</li> <li>yield</li> <li>Packing data</li> <li>rolls per case</li> <li>17mu</li> <li>±10%</li> <li>60%</li> <li>60</li> <li>60g</li> <li>60g</li> <li>64.3m²/kg</li> </ul>	~ roll length	300mtr
~ film thickness tolerance	~ roll length tolerance	+/- 2.0%
<ul> <li>core type</li> <li>core diameter</li> <li>38mm</li> <li>Technical data</li> <li>elongation at break</li> <li>dart impact</li> <li>pre-stretch</li> <li>tensile strength</li> <li>yield</li> <li>Packing data</li> <li>rolls per case</li> </ul> Extended 38mm 410% 60g 0-100% 64.3m²/kg	~ film thickness	17mu
~ core diameter  Technical data ~ elongation at break ~ dart impact 60g ~ pre-stretch ~ tensile strength ~ yield  Packing data ~ rolls per case  38mm  410% 60g 64.3m²/kg	~ film thickness tolerance	±10%
Technical data  ~ elongation at break  ~ dart impact  ~ pre-stretch  ~ tensile strength  ~ yield  Packing data  ~ rolls per case  410%  410%  60g  0-100%  64.3m²/kg	~ core type	Extended
<ul> <li>elongation at break</li> <li>dart impact</li> <li>60g</li> <li>pre-stretch</li> <li>tensile strength</li> <li>yield</li> <li>Packing data</li> <li>rolls per case</li> <li>410%</li> <li>410%</li> <li>60g</li> <li>0-100%</li> <li>47Mpa</li> <li>64.3m²/kg</li> </ul>		38mm
<ul> <li>elongation at break</li> <li>dart impact</li> <li>60g</li> <li>pre-stretch</li> <li>tensile strength</li> <li>yield</li> <li>Packing data</li> <li>rolls per case</li> <li>410%</li> <li>410%</li> <li>60g</li> <li>0-100%</li> <li>47Mpa</li> <li>64.3m²/kg</li> </ul>		
~ dart impact 60g ~ pre-stretch 0-100% ~ tensile strength 37Mpa ~ yield 64.3m²/kg  Packing data ~ rolls per case 6	Technical data	
~ pre-stretch 0-100% ~ tensile strength 37Mpa ~ yield 64.3m²/kg  Packing data ~ rolls per case 6	~ elongation at break	410%
~ tensile strength 37Mpa ~ yield 64.3m²/kg  Packing data ~ rolls per case 6	~ dart impact	60g
~ yield 64.3m²/kg  Packing data ~ rolls per case 6	~ pre-stretch	0-100%
Packing data ~ rolls per case 6	~ tensile strength	37Mpa
~ rolls per case 6		64.3m²/kg
~ rolls per case 6		
·	Packing data	
~ case weight 13.1kg	~ rolls per case	6
	~ case weight	13.1kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.