

KARTATAPE 1562




minipack®

Automatic Self-Sizing WAT Case Sealer



Semi-Automatic



Manual



Automatic

Automatic case sealer for water activated paper





KARTATAPE 1562

- *New patented taping heads (Evi), simple and reliable, completely in aluminium.*
- *It uses all types of gummed paper available on the market*
- *Simplified cartridge cleaning*
- *Jam-proof paper passage*
- *Simplified cutting adjustment*
- *Simplified water flow regulation*
- *Paper pressure adjustment*
- *30 meters per minute speed*
- *12 pieces per minute*
- *Completely closed with an opening hatch (Semiautomatic and automatic version)*


Kartatape M 1562




KARTATAPE 1562



Kartatape 1562





KARTATAPE 1562




Kartatape + Kartaform flap-closer



KARTATAPE 1562




Self-dimensioning




KARTATAPE 1562

- Motorized automatic self-regulation
- Instant format change
- Infinite maximum length measurement (max 800 mm for Kartaform + Kartatape version)



	Min	Max
Box Width	150 mm	600 mm
Box Height	150 mm	600 mm
Box Length	250 mm	∞ mm ((800 mm for Kartaform + Kartatape version)
Power supply	220V – 50 Hz	

Size reading devices




KARTATAPE 1562

- *Box stop for reading the dimensions*
- *Vertical photocells for instant height reading*
- *Horizontal photocells for instant width reading*
- *Connect directly to PLC and motors*
- *Pneumatic safety bars*



Innovative and patented Reel Holder




KARTATAPE 1562

- *Patented and easy lower reel change: the device rises automatically, allowing the reel to be changed quickly and safely*
- *The machine can be equipped with an acoustic and visual end-of-reel sensor (optional)*



Touch control and logic



KARTATAPE 1562

- *Omron Touch Controls*
- *Omron PLC*
- *Manual and automatic programs*
- *Alarms reset*
- *Speed change (three preinstalled speeds)*
- *Upper and lower head selection*
- *5 languages*



Continuous automatic water recycling



KARTATAPE 1562

- *Patented water recycling system*
- *Constant and adjustable water coating*
- *Up to 10 lt water tank on board*
- *Adjustable paper pressure*




Optionals

- *Kartaform preparation kit (for Semi-automatic)*
- *Lower / upper roll paper break warning*
- *Lower / upper roll paper end warning*
- *Idle output roller conveyer*
- *Centring module with motorized roller conveyer*
- *Mounting on wheels (minimum height 780).*
- *Possibility of single-taping machine management*
- *Direct brushless motorization for height adjustment*
- *Motorized outfeed roller conveyer*
- *Brushless motorization for height adjustment with regular belts*
- *Assistance box for remote connection*



KARTATAPE 1562

Water Activated Tape (WAT) - Eco-friendly



KARTATAPE 1562



The Water Activated Tape (WAT) or Kraft Tape, or gummed tape, binds instantly to both virgin and recycled fibre surfaces.

The dry adhesive is based on high quality starch or vegetable derivatives which give the tape an immediate trigger and grip on the cardboard generating an immediate destructive bond resulting in tamper-proof packaging

Water Activated Tape (WAT) - Benefit



KARTATAPE 1562


- *Less tape is used*
- *Only one strip is enough*
- *Strap avoid*



Why install Kartatape – With WAT you save money



KARTATAPE 1562



ADP28
Nastri adesivi polipropilene
silenzioso 35 micron avana RAJA
75mm x 66m

Qtà
24

Prezzo unitario
(IVA esclusa)
2,59 €
il rotolo

Prezzo totale
(IVA esclusa)
62,16 €

Medium price for **polypropylene tape**: € 0,0392 /mt



BG70
Rotoli di carta gommata standard
qualità 70g/mq RAJA 70mm x 200m

Qtà
12

Prezzo unitario
(IVA esclusa)
7,14 €
il rotolo


Prezzo totale
(IVA esclusa)
85,68 €

Medium price for **WAT**: € 0,0357/mt



- WAT can also be purchased in large batches and left in stock; rubber coating is “latent” and it is activated only by wetting it.

Why install Kartatape - Reliability




KARTATAPE 1562

- *All stress tests successfully passed.*
- *Careful assessment of the customer satisfaction*
- *Top-quality materials for all the components*



Why install Kartatape - Resistance




KARTATAPE 1562

A sealed package is safe as much as its seal is strong. For this reason, we expect the tape to withstand all the conditions to which the carton is exposed in high-speed sealing operations, during transport, storage, and final use.

The gummed paper tape creates a permanent proof tearing bond with the cardboard fibre of the box



Why install Kartatape - Safety



KARTATAPE 1562

*With its high adhesion and constant bond, the gummed paper tape becomes an **integral and therefore indissoluble part of the box** it seals; it is therefore extremely difficult to tamper with the seal except evidently.*

The use of customized tapes will avoid those situations where any break-in is covered by restoring the tape



Why install Kartatape - Ecology



KARTATAPE 1562

Gummed paper tape is a truly “green” product.

*Both the paper base and the starch-based adhesion formulation are **natural materials** and therefore are totally **biodegradable** as well as suitable for recycling.*


*By 31 **December 2025**, at least **65% by weight** of all packaging waste must be recycled.*

*By 31 **December 2030**, at least **70% by weight** of all packaging waste must be recycled.*

Custom and printed tapes are also produced with environmentally friendly water-based inks.



Why install Kartatape - Heat and cold resistance



KARTATAPE 1562

The gummed paper tape is easy to use and is effective in all weather conditions.

Adhesion is not affected by extreme levels of humidity or heat.

This flexibility is extremely valuable for goods that can be packed and sealed in hot environments.

Likewise, cartons can be satisfactorily sealed with gummed paper tape at normal or sub-zero ambient temperatures.

Packaging will not be affected by freezing or frozen storage.

There is no minimum temperature that can affect adhesion.

