

# RXT

## BATTERY POWERED STRAPPING TOOL



A professional lithium-ion powered strapping tool with flexible settings, wide tension range and compatibility with PP and PET strapping





# RXT

## BATTERY POWERED STRAPPING TOOL

### Main Features:

- > **Easy & Fast Operation**  
RXT is extremely easy to operate. Single-button automatic mode completes the strapping process in less than three seconds.
- > **Digital Touch Panel**
  - > Versatile design with auto, semi-auto, manual, and soft strapping.
  - > Fast and flexible settings for operation mode, tension force and sealing time.
  - > Battery charge level and troubleshooting guides.
- > **Brushless Motor Technology**
  - > A German-manufactured brushless direct-drive DC motor provides the highest level of accuracy and reliability.
  - > This state-of-art technology results in less maintenance and longer life time of the motor.
- > **Bosch® Battery and Charger**
  - > Bosch® high capacity battery provides up to 550 strapping cycles per charge for PP and up to 320 for PET.
  - > Rechargeable Bosch® battery for up to 1,000 charges.
- > **Simple Adjustments for Different Strapping**  
Only two strap guides have to be changed for applying different strap widths. The cooling time will be automatically adjusted to suit the tension.
- > **Friction Weld Sealing**  
Advanced friction weld sealing technology guarantees reliable joint and high seal efficiency for both PP and PET strapping.



- > **Robust Housing**  
Rugged construction provides outstanding impact resistance.
- > **Perfect Balance and Ergonomic Design**  
Ergonomic handle with non-slip design and wellbalanced structure for easy and effortless operation.

### Options:

- > Suspension bracket (static or swivel)
- > Base wear protection plate

**PP** Suitable for use with polypropylene strapping

**PET** Suitable for use with polyester strapping

Suitable for engineering industry applications

Heat weld seal - no need for metal seals

Strapping tension range up to 400kg

Suitable for brick/concrete industry applications

Battery powered

Suitable for timber industry applications

Total machine weight 4.4kg

Suitable for carton strapping applications



Digital control panel



Bosch battery & charger

### Specifications

	RXT13 RXT16	RXT19
Min/Max Tension:	40-250 kg	60-400 kg
Strap Widths:	RXT13 11 - 13mm RXT16 15 - 16mm	16 - 19mm
Min/Max PP Thickness:	0.55mm - 1.05mm	0.75mm - 1.30mm
Min/Max PET Thickness:	0.50mm - 1.05mm	0.60mm - 1.30mm
Machine Weight:	4.3 kg	4.4 kg
Battery:	Bosch® Li-Ion 18V 4.0Ah	
Battery Charger:	Bosch® 230v (220-240v) 50/60Hz	

\* Please note that the number of strapping cycles obtained from a full battery will vary depending on quality and specification of strap, length of slack taken up during tensioning, strap tension and sealing time settings, ambient conditions and operator technique.

