TECHNICAL DATA SHEET



BCE417 Blown Stretch Film

Product description	Stretch wrap film for manual use, on extended core
Product data	
~ raw material	LLDPE
~ colour	clear
~ roll width	400mm
~ roll width tolerance	-0mm/+5mm
~ roll length	300mtr
~ roll length tolerance	+/- 2.0%
~ film thickness	17mu
~ film thickness tolerance	-10/+0%
~ kinetic C.O.F.	0.400 - 0.721 (ASTM D1894-14)
~ static level	max. 15kV (715 static meter)
~ impact strength (drop dart)	2 (ASTM D1709-04)
~ nominal density	0.918g/cm³
~ yield	6.24g/lm
,	64.08m²/kg
~ outside diameter	92mm (target)
~ core type	cardboard
~ core inside diameter	38mm
~ core outside diameter	46mm
~ core length	580mm
Packing data	
~ rolls per case	6
~ total case weight	15.6kg
~ total case weight	13.0kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.