TECHNICAL DATA SHEET



ECO75X Self-Adhesive Kraft Paper Tape

| Product description | Kraft paper carton sealing tape for general packaging applications, hand-tearable and with good adhesion, while hotmelt adhesive makes this product an even more environmentally responsible option. |
|--------------------------|--|
| Product data | |
| ~ tape material | Natural kraft paper |
| ~ tape colour | brown |
| ~ tape weight | 57gsm |
| ~ tape thickness | 89mu |
| ~ adhesive | hotmelt |
| ~ roll width | 75mm (± 1.5mm) |
| ~ roll length | 50mtr (± 2.5%) |
| Technical data | |
| ~adhesion to steel | 6.5N/25mm |
| ~ tensile strength MD | 135N/25mm |
| ~ shear | 120 hours |
| ~ elongation at break | 7% |
| ~ temperature resistance | 60°C |
| Storage data | |
| ~ ambience | 23°C, 50% relative humidity, away from direct sunlight |
| ~ protection | Avoid damage to roll, especially edge cuts |
| | Keep in original packaging and avoid heavy stacking and impact |
| ~ shelf life | 12 months in above conditions |
| Usage data | |
| ~ ambience | If stored below 10°C must be conditioned to 10-40°C before use |
| Packaging data | |
| ~ rolls per case | 24 |
| ~ case weight | 9.4kg |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.