

# Grip Mailer Bag

## Mailing Bags 465 X 655mm

Date of issue 22/05/23

### Product Specification:

Length:	55mm
Width:	360mm
Pack Quantity:	500
Product Code:	G100044



Roll No	Film Width (cm)	Weight (g)	Average Thickness (Micron)	Width (mm)	Length (mm)	Guesset (mm)	Flap (mm)	Turn Over Top (mm)
<b>SPECS</b>	0	22.7729	35	465	655	0	80	0
<b>TOLERANCE</b>	± 1 cm	± %5	±%8 mic.	±10 mm	±10 mm	±5 mm	±5 mm	±5 mm
<b>RESULT</b>								
1	0	23,01	35	460	658	0	80	
2	0	23,35	35	463	656	0	80	
3	0	22,87	35	456	655	0	80	

<b>Product Specification:</b>	There should be no dirt, foreign material, scratches, unmelted raw materials, burns, tears, holes, wrinkles, herringbone appearance, haze and frosted glass on transparent films.
<b>Smell:</b>	Unless otherwise specified, it should be odorless and if there is a special demand, the product must be in the desired odor.
<b>Corona</b>	Corona should be complete in printed areas, corona weakness should not be seen, there should not be corona passing on corona-free surface.
<b>Print Side</b>	Print side should be on the desired surface according to the product feature. (Inner surface, outer surface, lamination etc.)
<b>Adhesion</b>	The final product should have good paint adhesion, no paint transfer and picking.
<b>Film Colour and Opacity</b>	The film color should match the pantone or the customer color / approval sample. Opacity must be in accordance with customer demand.
<b>Photocell Square Size</b>	For orders shipped in rolls, the photocell location must comply with the customer approved design.
<b>Templating</b>	When overlapping with the reference sample or chromoline (color output) specified by the customer, the prints should overlap or conform to the dimensions in the drawing.
<b>Print Color</b>	Print colors must match the customer's specified reference sample, chromoline (color output) or the specified pantone.
<b>General Print Appearance</b>	Prints should be clear, text should be legible, paleness and burr should not be seen. There should be no paint stains, reflections, tape marks, knocks or slippage in the print.
<b>Print Content</b>	The print should be exactly the same as the desired design.
<b>Roll Winding Direction</b>	The winding direction must be in accordance with customer requirements.
<b>Roll Winding</b>	Roll winding should be smooth and there should be no recesses or protrusions on the edges, and the rolls should not have wrinkles. The number of attachments should be determined according to customer demand.
<b>Packaging and Label</b>	The product must be packaged in such a way that it is not adversely affected by external factors with the packaging material requested by the customer. The information on the product label must be complete and accurate and must be in accordance with customer requirements.

### Palletisation

Bags per Pallet:	22,500
Cases per Pallet:	45