

Tegrabond® KR4810B-GSI Reinforced Tape

Product description	<p>Natural kraft carton tape with three-way fibreglass reinforcement and water activated adhesive.</p> <p>Used for top and bottom carton closure sealing, adhering well to recycled carton material and light-medium cartons.</p> <p>Gummed on inside of roll.</p>
Product data	
~ roll width	48mm
~ roll length	100mtr
~ core diameter	38mm
Construction	
~ top ply	33gsm natural kraft
~ bottom ply	40gsm natural kraft
~ adhesive	24gsm chemically grafted starch-based copolymer
~ MD reinforcement	839g (1-1-1-1/1-1-1-1) 110 fibreglass per 70mm at 15mm CD spacing
~ CD reinforcement	671g (1-1-1) 150 fibreglass, 27.5mm spacing at 44° angle
~ total base weight	125gsm
~ caliper	144mu
Technical data	
~ MD tensile strength	284N/cm ²
~ CD tensile strength	120N/cm ²
Adhesion	(using water heated to recommended 43.3 °C)
~ Fipago 2/0	58
~ Fipago 2/1	81
~ Fipago 5/0	83
~ Fipago 15/0	92
~ McCaurin	81

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.