



# SK10

Automation Grade	<b>SEMI</b>	Fully	Use Intensity	<b>LOW</b>	Medium	High
Format Setting	<b>MANUAL</b>	Automatic	Box Dimension	Small	<b>MEDIUM</b>	Large

## DATASHEET

SAFE • SUSTAINABLE • SIMPLE


## Semi-Automatic Case Sealer

The **SK10** is a new semi-automatic case sealing machine designed and engineered by SIAT specifically for medium fixed sized boxes. SK10 is the ideal case sealing machine for a variety of industries like food and beverage, chemical, clothing, textiles, electronics and furniture.

### KEY FEATURES

- ✓ **Practical** - Seals upper & lower flaps of cardboard cases or cartons
- ✓ **Added Protection** - Lockable electric isolation switch
- ✓ **Safety First** - Central emergency stop to work safety on both sides of the machine
- ✓ **Taping Heads** - Available with K11 or K12 taping heads
- ✓ **Simple Operation** - Intuitive and quick machine set-up
- ✓ **Quality Build** - Best-In-Class components with SIEMENS electrics
- ✓ **New feature** - Top taping head removable
- ✓ **Improved Design** - Quick release Taping Heads (Top & Bottom – No tools required)
- ✓ **CE compliant** - Engineered and produced in Italy according to EU safety standards

### MACHINE DIMENSIONS



Machine Dimensions			Standard Power Supply	
	Min (mm)	Max (mm)	380/415V - 50Hz - 3ph	
H Column	1.170	1.510	440V - 60Hz - 3ph	
H Bench	485	825	Amps	1,54
W	690	690	Power kW	0,13
W Bench	570	570	Phase	3Ph + PE
L	1.080	1.080		

# SK10



## DATASHEET

### Technical Data



Belt position	Bottom
Box Size	Medium
Min / Max box weight	2 - 30 kg
Default Taping Head	K11 for 2" = 50 mm
Alternative Taping Heads	K12 for 3" = 75 mm
Power Consumption (std.)	0,13 kw
Air Consumption (NL/Cycle)	-
Operator Side	Left (std.) / Right
Tape width (mm)	50 (std.) / 75
Tape Leg (mm)	70 (std.) / 50 / 30
Ingress Protection Code	IP54
Ambient Operating Temperature	5 – 40 °C
Maximum level of noise	Depending on tape quality

### Features


Removable Top Taping-Head	•
Removable Bottom Taping-Head	•
Adjustable Tape Leg	•
Pre-Installed & Easy-To-Mount	•
Adjustable Tape Contact Pressure	•
Autom. Box Format Setting	-
Flap Folding Function	-
Belt Speed Selection	-
Fully Automatic Operation	-
SIAT Taping-Logic on board	-

### MORE MACHINE DIMENSIONS

Length x Width	1.080 x 690
Workbench Width	570
Height H (std. legs)	1.170 – 1.510
Height H1 (std. legs + wheels AS77)	1.280 – 1.610
Height H2 (opt. legs AS80)	1.330 – 1.665
Height H3 (opt. legs AS80 + wheels AS77)	1.440 – 1.775
Workbench Height Z (std. legs)	485 – 825
Workbench Height Z1 (std. legs + wheels AS77)	595 – 935
Workbench Height Z2 (opt. legs AS80)	645 – 980
Workbench Height Z3 (opt. legs AS80 + wheels AS77)	755 – 1.090




### BOX DIMENSIONS & PRODUCTIVITY



\*140 mm with 50 mm taping head K11  
170 mm with 75 mm taping head K12

Box Dimensions	L (mm)	W (mm)	H (mm)
Min.	150	140*	90**
Max.	∞	500	500

\*\* 90 mm high box manageable with 30 mm tape leg  
100 mm high box manageable with 50 mm tape leg  
120 mm high box manageable with 70 mm tape leg




Max. production capacity:  
**Up to 1.200\* BPH**

\*Based on the shortest processible box length and provided an optimum continuous box infeed by the operator.

### PROCESSABLE TAPES

Base Material	PVC / OPP / PET / Paper*
Adhesive Type	Solvent / Hot Melt / Acrylic
Special Tape	Filament-Tape** / Safety-Seal-Tape***

\*with limitations \*\*special tape cutting blade required \*\*\*need of a test might be necessary



K11R / K12R	
A	Max. 410 mm
B	50 / 75 mm
C	76 mm

### BOX REQUIREMENTS

Quality result of the taped box depends on the general box quality and dimensional accuracy, as well as the quality of tape used.

Box Types: FEFCO 0201 – RSC  
*[other types may be possible as well]*

Adverse Impact Factors	Underfilling	Overfilling	Weak Boxes

### OPTIONS & ACCESSORIES

- Operation side "Right" (std. "Left")
- Special cutting blades filament-tape
- Taping Head for 75mm width
- Power Supply 220/230V – 50hz – 1ph
- Higher Legs
- Casters / Wheels
- Extendable Roller Conveyors
- Fix Roller Conveyors
- Box Holder
- Energy Saving Kit
- End/Break Tape Device

### MORE DETAILS

Videos and further information can be found on our website or SIAT Youtube channel.



SAFE • SUSTAINABLE • SIMPLE

SIAT.com