

# TEC 810-15

... the power to perform

**POWER  
ADHESIVES**

## HEAVY DUTY MID RANGE GLUE GUN

The **TEC 810-15** is setting a new standard in performance for a gun of this size.

With its compact design, full hand lever trigger, very fast warm up time of only 2 to 3 minutes and with an impressive glue output of over 2 kilos per hour (depending on formulation). The **TEC 810-15** will soon establish itself as the world leader in the mid range section of the market.

The **TEC 810-15** has many unique features such as easy to change thermostats to adjust the gun's temperature to dispense the different types of hot melt and low melt adhesives available. An illuminated on off switch and a narrow profile handle with a soft feel grip making it an exceptionally comfortable and easy gun to use. It has an adjustable trigger stroke to accommodate most size hands and a detachable stand which incorporates a nozzle spanner.

The **TEC 810-15** dispenses 15mm x 300mm high performance **TECBOND** hot melt glue sticks, and can dispense a third more molten glue from each trigger-pull against a similar size 12mm gun and holds 70% more glue.

The **TEC 810-15** is built to comply with world wide industrial and electrical safety standards and covered by a full one year warranty.



### FEATURES



Illuminated on-off switch and detachable base stand incorporating nozzle spanner



Open breach for easy cleaning and trigger stroke adjustable screw to suit any size hand



Full hand lever trigger and narrow profile handle with soft feel grip



Easy change temperature thermostats, to suit different types of hotmelt and lowmelt

**FOR OUR FULL PRODUCT RANGE PLEASE VISIT OUR WEBSITE**  
[www.poweradhesives.com](http://www.poweradhesives.com)

## SPECIFICATION

VOLTAGE	230V OR 110 - 120V 50-60HZ
HEATER	TEC 810-15 300W High performance stainless steel cartridge
TEMP CONTROL	Preset Thermostat (fitted with 195°C) with safety thermal fuse. Other easy change thermostat available.
WEIGHT	0.5kg
POWER CABLE	2m 3 core rubber sheathed cable with plug fitted, UK, European, Australian, Swiss & USA, versions available.
MELT RATE	Over 2kg/hr depending on adhesive & temperature
ADHESIVE SIZE	TECBOND 15mm Glue Stick

## OPTIONAL NOZZLES



The TEC 810-15 is supplied with a one piece one hole extension nozzle with 2mm orifice (part number ADJ010) Optional nozzle caps are available for specialised purposes and to speed up adhesive application.

REF	PART No	TYPE	DESCRIPTION
1	ANZ999	Adaptor	This part is needed to use No's 2,3&5 caps
2	MNZ013	2 Hole	2 Parallel Adhesive lines 10mm apart
3	MNZ027	3 Hole	3 Parallel Adhesive lines 5mm apart
4	ADJ004	Slotted Spreader	Allows a 12mm wide spread of glue
5	PA5032	L Nozzle	Fast full overlap carton sealing



## OPTIONAL ACCESSORIES



**TEC SB/1200 Spring Balance** with a maximum extended cord length of 1.6m designed to minimise operator fatigue. It also increases productivity and reduces the chance of accidental damage to the applicator.



**TEC Optional metal stand** Part No MDC009 ideal for use on work surface or wall mounted.



## ADHESIVE RE-ORDER



**TECBOND** high performance 15mm adhesive sticks, specially designed for use in the TEC 810-15, available to bond virtually any material. The range provides variations in setting time heat resistance and viscosity to suit every application.



**TECMAT Silicon Rubber Drip Mat** can be used underneath the TEC 810-15 gun to protect work surfaces against damage caused by molten hotmelt adhesive

Designed and built to comply with EN 60335-2-45

